



TJ LRF Series

Handheld Thermal Imaging Monocular

Welcome to the Big Screens



Introduction

Embark on nighttime explorations with the TJ LRF Series, a top pick for hunters. Equipped with exceptional thermal imaging technology, this device features a high-sensitivity infrared detector that enables clear night vision. The Full-HD display enhances these benefits, while two-hand operation, laser ranging, video recording, and a 12-hour battery life make it the perfect companion for nighttime escapades.

Features

- o 12 μ m advanced thermal detector, NETD down to 20mK.
- o Full-HD 1920 \times 1080 AMOLED display.
- o Laser Range Finder up to 1000m.
- o Unique button and battery design enables blind installation in the dark.
- o Adaptable for left and right-handed use.
- o Video recording including synced audio.
- o IP67, 12 hours of operation.

Applications

- o Night Hunting
- o Search & Rescue
- o Law Enforcement
- o Personal Security



Specifications



Product model	TJ420L	TJ430L	TJ630L	TJ650L
Sensor				
Type	Uncooled VOx Infrared Detector, 8 to 14μm			
Resolution	400×300@12μm		640×512@12μm	
NETD	25mK		20mK	
Frame rate	50Hz			
Lens				
Objective lens	25mm, F1.0	35mm, F1.0		50mm, F1.0
Field of view	11°×8.2°	7.9°×5.9°	12.5°×10°	8.8°×7°
FOV m@100m	19×14	14×10	22×17	15×12
Magnification	3.04x~12.16x	4.25x~17.0x	2.66x~21.28x	3.79x~30.32x
Detection range	1300m/1400yd	1800m/1950yd		2600m/2800yd
Focus	Manual			
Display				
Display type	0.39" AMOLED 1920×1080			
Color palettes	White Hot, Black Hot, Red Hot, Green Hot, Iron Red, Blue Hot, Sepia			
Eyepiece	Eye relief: 16mm; Diopter: -6 to +6; Zoom: 18x			
Hardware				
Laser rangefinder	1000m/1090yd			
WIFI	2.4G, 5G			
Interface	USB-C (Power supply/USB2.0)			
Others	Microphone, Compass, Gyroscope, Bluetooth			
System				
Recording function	Photo/Video (Audio recording included)			
Memory capacity	32GB		64GB	
Power				
Battery type	2 Replaceable 18650 Batteries			
Operating time	12 hours		10 hours	
Environmental				
Operating temp.	-20°C to 50°C / -4°F to +122°F			
Encapsulation	IP67			
Physical				
Weight (g/oz)	558/19.68	583/20.56	581/20.49	625/22.05
Size (mm/in)	234×97×66/ 9.21×3.82×2.60	243×97×66/ 9.57×3.82×2.60	234×97×66/ 9.21×3.82×2.60	243×97×66/ 9.57×3.82×2.60
Standard	Device, 18650 Battery ×2, Battery Charger, 5V 2A Adapter (US, UK, Australia, and Europe), USB-A to USB-C Cable, Quick Start Guide, Warranty Card			
Optional	Bluetooth Remote Control, 18650 Battery			

* Product performance is based on testing in a controlled laboratory environment. Your test results may vary due to several external and environmental factors.
All specifications are subject to the actual product. The manufacturer reserves the right to modify technical specifications without notice or liability to you.